

Acer PD725P

Der Leuchtstarke

- Die zukunftsweisende DLP Technologie garantiert beste Bildqualität und brillante Farben und ist die optimale Präsentationslösung für Konferenzen und Trainings.
- Der hohe Kontrast von 2000:1 und die Helligkeit von 3600 ANSI Lumen garantieren ein gestochen scharfes und kontrastreiches Bild.
- Die geringe Geräuschentwicklung von nur 32 dB (27 dB im Eco-Mode) erlaubt die volle Konzentration auf Präsentationsinhalte, insbesondere in kleineren Gruppen.



Technische Daten

Specifications	Acer PD725P
Artikel-Nr.	EY.J1801.001
Projection System:	DLP™
Resolution:	Native XGA (1,024 x 768), Maximum UXGA (1,600 x 1,200)
Computer Compatibility:	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards UXGASXGA, SVGA, VGA (resizing)
Video Compatibility:	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio:	4:3 (Native), 16:9
Contrast Ratio	2000:1
Displayable Colors:	16.7 Million Colors
Brightness:	3,600 ANSI Lumens (standard), 2,900 ANSI Lumens (ECO)
Projection Lens:	F / 2.4 ~ 2.6, f = 28.0 ~ 33.6 mm, 1:1.2 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal):	24.6" (0.625m) ~ 300" (7.62m)
Projection Distance:	3.94' (1.2m) ~ 40' (12.2m)
Throw Ratio:	49"@2m
Lamp Type:	300 W User Replaceable P-VIP Lamp
Lamp Life:	2,000 Hours (standard), 3,000 Hours (ECO)
Keystone Correction:	+/-16 Degrees, Vertical & Horizontal Keystone Correction
Projection Mode:	Front, Rear, Front-Ceiling, Rear-Ceiling
Audio:	2 Internal Speakers each with 2 watts Output
Weight:	3.4Kg
Dimension:	330 x 269 x 100 mm
Remote Control:	Laser Pointer & Mouse function & PgUp/PgDn function
Picture in Picture:	Yes
Power Supply:	AC Input 100~240V auto-switching power supply
Power Consumption:	384 Watts
Noise Level:	32 dB (standard mode), 27 dB (ECO mode)
Uniformity:	85%
I/O Connectors:	Computer Input: 1 HDB 15-Pin D-Sub, 1 3.5mm Audio Mini Jack, 1 RS232 Connector, 1 29 pin DVI-I Connector AV Input: 3 RCA Jack (YCbCr), 1 Composite Video, 1 S-Video Mini DIN, 1 3.5mm Audio Mini Jack, 1 29 pin DVI-I Connector Output: 1 15-Pin D-Sub for Monitor, 1 USB Connector for Remote Computer Control, 1 3.5mm Audio Mini Jack
Standard Accessories:	AC Power Cord, VGA Cable, Composite Video Cable, S-Video Cable, Component Cable, USB Cable, Audio Cable, DVI to VGA Cable, Remote Control with Laser Pointer & Mouse & PgUp/PgOn, Batteries, User's Guide (CD-ROM), Quick Start Card, Lens Cap, Carrying Case